



High Power Die Casting Ip65 400w Outdoor Led Flood Lights

Our Product Introduction

for more products please visit us on solarledstreet-light.com

Basic Information

- Place of Origin: China
- Brand Name: Yahua lighting
- Certification: CE ROHS
- Model Number: YHZ-FLCOB
- Minimum Order Quantity: 10pcs
- Price: USD85-USD88.00/pc
- Packaging Details: Foam+carton
- Delivery Time: 5-8 Days
- Payment Terms: L/C, D/A, D/P, Western Union, T/T, MoneyGram
- Supply Ability: 3000pcs



Product Specification

- Light Source: LED
- Color: Black
- Material: Aluminum Housing
- Input Voltage(v): AC85-265V
- Cri (ra>): 80
- Working Lifetime(hour): 50000
- Warranty(year): 3
- Working Temperature(°C): -30 - 60
- Ip Rating: IP65
- Led Light Source: Epistar
- Highlight: 400w Outdoor Led Flood Lights, Ip65 Outdoor Led Flood Lights

500W



More Images



Product Description

High power Ip65 waterproof outdoor cob Die-casting aluminum 300w 400w 500w led floodlight

LED flood light

1. Working Voltage : AC85V- 265V
2. Power: 200w,300w,400w,500w,600w
3. IP65 OEM welcome
4. Die Casting Aluminum body

Outdoor led floodlight

Feature:

1. High brightness with good heat sink
2. Easy installation and maintenance
3. Tempered glass: heat-proof, crash-proof
4. Reflector in pure aluminum
5. Steel bracket
6. Stainless steel external nuts and screws
7. Heat-resistant silicon rubber seal ring
8. Die casting Aluminum Body
9. Multiple-color for customers to choose: Red, green, blue, yellow and white
10. Power consumption as low as 10W while lumen output equivalent to 50W halogen bulb
11. No UV, IR or other deleterious radiation.
12. No mercury

Model	YHZ-FLCOB		
power	400W	500W	600W
Dimension (MM)	627*356*100	832*360*100	970*360*100
Light Source	8x 50w LEDs	10x50w LEDs	12x 50w LEDs
LED brand	Epistar	Epistar	Epistar
LED DRIVER	High Power CN	High Power CN	High Power CN
Input Voltage	AC85-265V	AC85-265V	AC85-265V
Frequency Range	50/60Hz	50/60Hz	50/60Hz
Power Factor (PF)	> 0.9	> 0.9	> 0.9
Led Luminous Efficiency	≥110 lm/W	≥110 lm/W	≥110 lm/W
Color Temperature	2600-6500K	2600-6500K	2600-6500K
Working Temperature	-30°C~+55°C	-30°C~+55°C	-30°C~+55°C
Beam angle	120°	120°	120°
IP Rating	IP65	IP65	IP65
Working Life	50000H	50000H	50000H
Materials	Die-casting aluminum, glass and surface polyester electrostatic spraying		




500W






 **Shaanxi Yahua Lighting Electric Equipment Co., Ltd.**

 +86 2981028690

 summer@sxyhzm.com

 solarledstreet-light.com

No.1 Xinxu Avenue New Industrial Park, Hi-tech Zone, Xi'an, China