Indoor PC Reflector 100W 150W 200w Led High Bay Lights

Basic Information

- Place of Origin: China
- Brand Name: Yahua lighting
- Certification: CE ROHS
- Model Number: YHZ-HBLPC
- Minimum Order Quantity: 1pc
- Price: USD48.00-USD50.00
- Packaging Details: Foam+Carton
- Delivery Time: 5-8Days
- Payment Terms: D/A, D/P, T/T, Western Union, MoneyGram, L/C
- Supply Ability: 1000PCS

Product Specification

- Material: Aluminum Body+PC Reflector
- Color Temperature: 5500K
- Beam Angle: 60,90 120 Degree
- Lumen Efficiency: 140LM/W
- Warranty: 3-5 Years
- Application: Workshop, Shoppingmall, Airport, Indoor Building
- Highlight: **200w Led High Bay Lights**,
                              150W Led High Bay Lights,
                              100w Led High Bay Lights

More Images

Product Description

High bright Factory workshop warehouse industrial lighting 100W 150W 200W led high bay light with PC reflector

♦ Comsuption Range: 100W 150W 200W
♦ Light Source: famous chips brand for Choice
♦ Driver: Meanwell/ Inventronics/ Other China Brand CE driver
♦ Light Housing: Unique patented design, 60°120° beam angle suitable for different application place, aluminum materials with aluminum alloy surface treatment technology
♦ Has air lead structure for heat-sink make better heat dissipation
♦ Installation: Rings, hook or iron chain
♦ Work temperature: -20°C ~ +45°C
♦ IP 65 Grade, waterproof suitable for indoor and outdoor

Application

1. Warehouse Lighting, Factory Lighting, Industrial Lighting
2. Garage Lighting, Workshop Lighting
3. Outdoor Area Lighting, High Mast Lighting
4. Supermarket Lighting, Store Lighting
5. Tunnel Lighting, Bridge Lighting
6. Gas Station Lighting

Power	60W	100W	150W	200W	300W	400W
Model	YHZ-HBLA-60W	YHZ-HBLA-100W	YHZ-HBLA-150W	YHZ-HBLA-200W	YHZ-HBLA-300W	YHZ-HBLA-400W
Replacement	HPS 150W	HPS 200W	HPS 300W	HPS 400W	HPS 600W	HPS 1000W
Luminous Flux	7800lm	13000lm	19500lm	26000lm	36000lm	48000lm
Light Source	SMD LED					
Luminous Efficacy	130lm/W					
IP	48					
Voltage	85-277VAC/50-60HZ					
CRI	>80					
Control System	APP, remote control, touch screen, light control and other control options available					
Operation Temp.	-40 to +60					
CCT	2700K SW/3000K WW/4100K NW/5000K DW/5700K CW					
Life Span	50,000 hours at 25					
Dimming	Dimmable Option					
Accessories	Different installation accessories:A - Ring mounting;B - Bracket mounting					
Beam Angle	120°(transparent,matte) 60° 90° (lens)					
PF	>0.95					
Cover	Transparent,matte,lens available					
Warranty	3-5 Years					