HLG Meanwell Driver 200w 150w High Bay Led Lighting

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:

Our Product Introduction

for more products please visit us on solarledstreet-light.com

- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:
- YHZ-HBLC 1pc USD48.00-50.00/pc Foam+Carton 5-8Days D/A, D/P, T/T, Western Union, MoneyGram, L/C 1000pcs



Product Specification

- Material:
- Input Voltage(V):
- Color Temperature:
- Driver:
- Item Type:
- Warranty:
- Highlight:

Aluminum

China

Yahua lighting

CE ROHS

85v-277V

- 3000K/4000K/5000K/6000K
- HLG Meanwell
 - Indoor Commerical High Bay Light
- 3-5 Years
- 150w high bay led lighting, 200w high bay led lighting, 150w led ufo high bay



More Images



Product Description

High efficient heat pipe commerical induction 200w 150w led high bay light linear high bay lighting

1.CE ROHS TUV Certified

2.Low power consumption, high luminous efficiency and energy saving

3. Easy to install and use.

4. High efficiency, high accuracy, and long-life constant current LED power supply, the efficiency can reach as high as 91%

5.No risk of mercury emission, No UV or RF interfcernce, No mercury or lead, environmental protection

6. High heat conductivity, low luminous decay, pure light color and no ghosting.

7.Integrative design for heat sink and housing; The LED is closely connected to the surface. The heat From the LED is removed through the heat dissipation wing and also by air ventilation.

8. The surface is passed through anodic oxidation treatment. Its structure is compact and beautiful.

9. Using high quality aluminum for production, fine workmanship, elegant appearance

10. Recommend the use of warm white and white. Long life span with 50,000 hrs.

Technical Data sheet:

Power	60W	100W	150W	200W	300W	400W
Model	YHZ-HBLA-	YHZ-HBLA-	YHZ-HBLA-	YHZ-HBLA-	YHZ-HBLA-	YHZ-HBLA-
	60W	100W	150W	200W	300W	400W
Replacement	HPS 150W	HPS 200W	HPS 300W	HPS 400W	HPS 600W	HPS 1000W
Luminous	7800lm	13000lm	19500lm	26000lm	36000lm	48000lm
Flux						
Light Source	SMD LED					
Luminous	130lm/W					
Efficacy	130111/100					
IP	48					
Voltage	85-277VAC/50-60HZ					
CRI	>80					
Control	APP, remote control, touch screen, light control and other control options available					
System						
Operation	-40 to +60°C					
Temp.						
CCT	2700K SW/3000K WW/4100K NW/5000K DW/5700K CW					
Life Span	50,000 hours at 25 °C					
Dimming	Dimmable Option					
Accessories	Different installation accessories: A - Ring mounting; B - Bracket mounting					
Beam Angle	120°(transparent,matte) 60° 90° (lens)					
PF	>0.95					
Cover	Transparent,matte,lens available					
Warranty	3-5 Years					

PC Cooler heatsink use the HDT Technology:

Pure Copper heatpipes directly touch the heat souce which could quickly transer heat to the heatsink with the heat transfer rate over 200 times of the aluminum radiator.







