



High Bright LED Street Light 3000K-6500K

Basic Information

Place of Origin: Guangdong China

Brand Name: high Lumen Led street light
 Certification: EMC, RoHS,CE, LVD

Model Number: YH-SLMinimum Order 10

Quantity:

• Price: USD19-49

• Packaging Details: Foam + carton plus + wooden case

• Delivery Time: 3-7days

• Payment Terms: T/T, Wester union, Paypal, Credit Card

• Supply Ability: 8000PCS/Month



Product Specification

Input Voltage(V): AC 85V-265V (± 10%)

Color Temperature: 3000K- 6500K
 Line Diameter: 3*0.75 0.3m

CRI: >80Battery: 3 Years

IP Rating: IP66 WaterproofLight Source: SMD3030,SMD5050

• Life Span: 50,000hrs

• Highlight: IP66 Bright LED Street Light,

3000K-6500K Bright LED Street Light, CRI 80 Bright LED Street Light



More Images



Product Description

Features:

- 1. Ingress Protection: The LED Street Luminaire boasts an IP67 rating, guaranteeing its resilience against dust and water intrusion. It is meticulously engineered to withstand a wide range of challenging outdoor conditions.
- 2. Power Input: Designed to operate within an input voltage range of AC 85V-265V (±10%), this luminaire offers versatility and compatibility with various power sources, accommodating diverse electrical configurations.
- 3. Battery Life: The IP65-rated LED Street Luminaire is equipped with a robust battery boasting a lifespan of 3 years. This ensures prolonged and dependable performance without the need for frequent battery replacements.
- 4. Service Life: With an impressive service life of 50,000 hours, this LED Street Luminaire provides a durable lighting solution, effectively reducing maintenance and replacement costs over time.
- 5. Material Composition: Crafted from premium alloy, the LED Street Luminaire guarantees exceptional durability and efficient heat dissipation. This choice of materials enhances the luminaire's longevity, ensuring optimal performance even in demanding conditions.

Product Name	LED street light			
Wattage	30W/50W/70W/100W/150W/200W/240W/300W/320W			
Voltage	100-277vac/50-60hz; 200-480vac/50-60hz			
Luminous efficency	130lm/w, 150lm/w, 160lm/w available			
CRI	85			
Sensor	Timer control, motion sensor, photoelectric sensor, three-in-one dimming, Wifi Zigbee connection, photoelectric + timer control, 3-step dimming, GPRS, 3G/4G, Bluetooth, PLC and smart			
	motion sensors. microwave sensor			
default setting	The brightness is 100%, the microwave sensitivity is 75%, and the holding time is 5 minutes. Start illumination 50LUX, continuous brightness 30%, duration 30 minutes.			
Product size	560x200x98mm/610x245x98mm/660x245x98mm/714x340 x98mm			
Material	Die-cast aluminum + tempered glass + 316 stainless steel screws			
Operation Temp	-40-+50°C			
CCT	2700K/3000K/4100K/5000K/6500K			
IP	IP66/IP68			
Warranty	5 years			







No.1 Xinxi Avenue New Industrial Park, Hi-tech Zone, Xi'an, China